

Features



- Trench Power LV MOSFET technology
- High Density Cell Design for Low $R_{DS(ON)}$
- High Speed switching

Product Summary


V_{DS}	$R_{DS(ON)}$ TYP	I_D
120V	220mΩ@10V	3A
	240mΩ@4.5V	

Application

- CoBattery protection
- Load switch
- Power management



Schematic diagram



1C03: Device code

Marking and pin assignment



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)







Symbol	Parameter	Rating	Unit
Common Ratings (TC=25°C Unless Otherwise Noted)			
V_{DS}	Drain-Source Breakdown Voltage	120	V
V_{GS}	Gate-Source Voltage	±20	V
T_J	Maximum Junction Temperature	150	°C
T_{STG}	Storage Temperature Range	-50 to 155	°C
I_S	Diode Continuous Forward Current	$T_c=25^\circ\text{C}$ 3	A
Mounted on Large Heat Sink			
I_{DM}	Pulse Drain Current Tested	$T_c=25^\circ\text{C}$ 12	A
I_D	Continuous Drain Current	$T_c=25^\circ\text{C}$ 3	A
P_D	Maximum Power Dissipation	$T_c=25^\circ\text{C}$ 0.3	W
$R_{\theta JA}$	Thermal Resistance Junction-Ambient	150	°C/W


Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MLS1C03	SOT-23	1C03	3,000	45,000	180,000	7"reel

Electrical Characteristics (T _J =25°C unless otherwise noted)						
Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Electrical Characteristics @ T _J = 25°C (unless otherwise stated)						
B _{V(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	120	--	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =120V, V _{GS} =0V	--	--	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.2	1.8	2.5	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =10V, I _D =3A	--	220	270	mΩ
		V _{GS} =4.5V, I _D =2A	--	240	300	mΩ
Dynamic Electrical Characteristics @ T _J = 25°C (unless otherwise stated)						
C _{ISS}	Input Capacitance	V _{DS} =50V, V _{GS} =0V, f=1MHz	--	124	--	pF
C _{OSS}	Output Capacitance		--	33	--	pF
C _{RSS}	Reverse Transfer Capacitance		--	4.3	--	pF
Switching Characteristics						
Q _g	Total Gate Charge	V _{DS} =50V, I _D =2A, V _{GS} =10V	--	2.3	--	nC
Q _{gs}	Gate Source Charge		--	0.4	--	nC
Q _{gd}	Gate Drain Charge		--	0.7	--	nC
t _{d(on)}	Turn-on Delay Time	V _{DS} =50V, I _D =2A, V _{GS} =10V, R _G =2Ω	--	8.3	--	nS
t _r	Turn-on Rise Time		--	1.5	--	nS
t _{d(off)}	Turn-Off Delay Time		--	6.1	--	nS
t _f	Turn-Off Fall Time		--	0.72	--	nS
Source-Drain Diode Characteristics						
V _{SD}	Forward on voltage	T _J =25°C, I _S =3A	--	--	1.2	V

Typical Operating Characteristics



SOT-23 Package information


Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E1	2.250	2.550	0.088	0.100
E	1.200	1.400	0.047	0.055
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°