

Features


- Trench Power LV MOSFET technology
- High Power and current handing capability

Product Summary

V_{DS}	$R_{DS(ON)}$ TYP	I_D
40V	30mΩ@10V	6A
	40mΩ@4.5V	



Application

- PWM application
- Load switch



S18: Device code

Marking and pin assignment



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
--------	-----------	--------	------

Common Ratings (TC=25°C Unless Otherwise Noted)

V _{DS}	Drain-Source Breakdown Voltage		40	V
V _{GS}	Gate-Source Voltage		±20	V
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range		-50 to 150	°C
I _S	Diode Continuous Forward Current	Tc=25°C	6	A

Mounted on Large Heat Sink

I_{DM}	Pulse Drain Current Tested	$T_C=25^{\circ}C$	20	A
I_D	Continuous Drain Current	$T_C=25^{\circ}C$	6	A
P_D	Maximum Power Dissipation	$T_C=25^{\circ}C$	1.2	W
$R_{\theta JA}$	Thermal Resistance Junction-Ambient		104	°C/W

Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MLS2318	SOT-23	S18	3,000	45,000	180,000	7"reel

Electrical Characteristics (T_J=25 °C unless otherwise noted)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Electrical Characteristics @ T_J = 25 °C (unless otherwise stated)						
BV _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	40	--	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =40V, V _{GS} =0V	--	--	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.0	1.5	2.5	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =10V, I _D =5A	--	30	40	mΩ
		V _{GS} =4.5V, I _D =4A	--	40	58	mΩ

Dynamic Electrical Characteristics @ T_J = 25 °C (unless otherwise stated)

C _{ISS}	Input Capacitance	V _{DS} =10V, V _{GS} =0V, f=1MHz	--	490	--	pF
C _{OSS}	Output Capacitance		--	90	--	pF
C _{RSS}	Reverse Transfer Capacitance		--	70	--	pF







Switching Characteristics

Q _g	Total Gate Charge	V _{DS} =10V, I _D =4.5A, V _{GS} =4.5V	--	5.2	--	nC
Q _{gs}	Gate Source Charge		--	1.0	--	nC
Q _{gd}	Gate Drain Charge		--	1.3	--	nC
t _{d(on)}	Turn-on Delay Time	V _{DD} =20V, R _L =2Ω, V _{GS} =10V, R _G =3Ω	--	13	--	nS
t _r	Turn-on Rise Time		--	54	--	nS
t _{d(off)}	Turn-Off Delay Time		--	18	--	nS
t _f	Turn-Off Fall Time		--	11	--	nS


Source- Drain Diode Characteristics

V _{SD}	Forward on voltage	T _J =25 °C, I _S =6A	--	--	1.2	V
-----------------	--------------------	---	----	----	-----	---

Typical Operating Characteristics



SOT-23 Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E1	2.250	2.550	0.088	0.100
E	1.200	1.400	0.047	0.055
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°