

## Features




- Trench Power LV MOSFET technology
- High Power and current handing capability

## Product Summary

| $V_{DS}$ | $R_{DS(ON)}$ MAX | $I_D$ MAX |
|----------|------------------|-----------|
| 20V      | 380mΩ@4.5V       | 0.75A     |
|          | 450mΩ@2.5V       |           |

## Application

- Load/Power Switching
- Interfacing Switching
- Logic Level Shift



Marking and pin assignment



Halogen-Free







| Absolute Maximum Ratings (TA=25°C unless otherwise noted) |                                        |         |            |      |
|-----------------------------------------------------------|----------------------------------------|---------|------------|------|
| Symbol                                                    | Parameter                              |         | Rating     | Unit |
| Common Ratings (TC=25°C Unless Otherwise Noted)           |                                        |         |            |      |
| V <sub>DS</sub>                                           | Drain-Source Breakdown Voltage         |         | 20         | V    |
| V <sub>GS</sub>                                           | Gate-Source Voltage                    |         | ±12        | V    |
| T <sub>J</sub>                                            | Maximum Junction Temperature           |         | 150        | °C   |
| T <sub>STG</sub>                                          | Storage Temperature Range              |         | -50 to 155 | °C   |
| I <sub>S</sub>                                            | Diode Continuous Forward Current       | Tc=25°C | 0.75       | A    |
| Mounted on Large Heat Sink                                |                                        |         |            |      |
| I <sub>BM</sub>                                           | Pulse Drain Current Tested             | Tc=25°C | 3          | A    |
| I <sub>b</sub>                                            | Continuous Drain Current               | Tc=25°C | 0.75       | A    |
| P <sub>D</sub>                                            | Maximum Power Dissipation              | Tc=25°C | 0.15       | W    |
| R <sub>θJA</sub>                                          | Thermal Resistance Junction-to-Ambient |         | 833        | °C/W |

| Ordering Information (Example) |         |         |                      |                         |                            |               |
|--------------------------------|---------|---------|----------------------|-------------------------|----------------------------|---------------|
| Type                           | Package | Marking | Minimum Package(pcs) | Inner Box Quantity(pcs) | Outer Carton Quantity(pcs) | Delivery Mode |
| MLS3134KT                      | SOT-523 | 34K     | 3,000                | 45,000                  | 180,000                    | 7" reel       |




| Electrical Characteristics (T <sub>J</sub> =25°C unless otherwise noted)             |                                  |                                                                                        |      |      |      |      |
|--------------------------------------------------------------------------------------|----------------------------------|----------------------------------------------------------------------------------------|------|------|------|------|
| Symbol                                                                               | Parameter                        | Condition                                                                              | Min  | Typ  | Max  | Unit |
| Static Electrical Characteristics @ T <sub>J</sub> = 25°C (unless otherwise stated)  |                                  |                                                                                        |      |      |      |      |
| B <sub>V(BR)DSS</sub>                                                                | Drain-Source Breakdown Voltage   | V <sub>GS</sub> =0V, I <sub>D</sub> =250μA                                             | 20   | --   | --   | V    |
| I <sub>DSS</sub>                                                                     | Zero Gate Voltage Drain Current  | V <sub>DS</sub> =20V, V <sub>GS</sub> =0V                                              | --   | --   | 1    | μA   |
| I <sub>GSS</sub>                                                                     | Gate-Body Leakage Current        | V <sub>GS</sub> =±10V, V <sub>DS</sub> =0V                                             | --   | --   | ±20  | μA   |
| V <sub>GS(th)</sub>                                                                  | Gate Threshold Voltage           | V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA                               | 0.35 | 0.70 | 1.10 | V    |
| R <sub>DS(on)</sub>                                                                  | Drain-Source On-State Resistance | V <sub>GS</sub> =4.5V, I <sub>D</sub> =0.65A                                           | --   | 135  | 380  | mΩ   |
|                                                                                      |                                  | V <sub>GS</sub> =2.5V, I <sub>D</sub> =0.55A                                           | --   | 163  | 450  | mΩ   |
|                                                                                      |                                  | V <sub>GS</sub> =1.8V, I <sub>D</sub> =0.45A                                           | --   | 200  | 800  | mΩ   |
| Dynamic Electrical Characteristics @ T <sub>J</sub> = 25°C (unless otherwise stated) |                                  |                                                                                        |      |      |      |      |
| C <sub>ISS</sub>                                                                     | Input Capacitance                | V <sub>DS</sub> =10V, V <sub>GS</sub> =0V, f=1MHz                                      | --   | 33   | --   | pF   |
| C <sub>OSS</sub>                                                                     | Output Capacitance               |                                                                                        | --   | 21   | --   | pF   |
| C <sub>RSS</sub>                                                                     | Reverse Transfer Capacitance     |                                                                                        | --   | 10   | --   | pF   |
| Switching Characteristics                                                            |                                  |                                                                                        |      |      |      |      |
| Q <sub>g</sub>                                                                       | Total Gate Charge                | V <sub>DS</sub> =10V, I <sub>D</sub> =0.5A, V <sub>GS</sub> =4.5V                      | --   | 0.8  | --   | nC   |
| Q <sub>gs</sub>                                                                      | Gate Source Charge               |                                                                                        | --   | 0.3  | --   | nC   |
| Q <sub>gd</sub>                                                                      | Gate Drain Charge                |                                                                                        | --   | 0.17 | --   | nC   |
| t <sub>d(on)</sub>                                                                   | Turn-on Delay Time               | V <sub>DD</sub> =10V, I <sub>D</sub> =0.5A, V <sub>GS</sub> =4.5V, R <sub>G</sub> =10Ω | --   | 4.2  | --   | nS   |
| t <sub>r</sub>                                                                       | Turn-on Rise Time                |                                                                                        | --   | 19.1 | --   | nS   |
| t <sub>d(off)</sub>                                                                  | Turn-Off Delay Time              |                                                                                        | --   | 10.3 | --   | nS   |
| t <sub>f</sub>                                                                       | Turn-Off Fall Time               |                                                                                        | --   | 24   | --   | nS   |
| Source- Drain Diode Characteristics                                                  |                                  |                                                                                        |      |      |      |      |
| V <sub>SD</sub>                                                                      | Forward on voltage               | T <sub>J</sub> =25°C, I <sub>S</sub> =0.75A                                            | --   | --   | 1.2  | V    |

## Typical Operating Characteristics



**SOT-523 Package information**



| Symbol | Dimensions in Millimeters(mm) |       | Dimensions In Inches |       |
|--------|-------------------------------|-------|----------------------|-------|
|        | Min                           | Max   | Min                  | Max   |
| A      | 0.700                         | 0.900 | 0.028                | 0.035 |
| A1     | 0.000                         | 0.100 | 0.000                | 0.004 |
| A2     | 0.700                         | 0.800 | 0.028                | 0.031 |
| b1     | 0.150                         | 0.250 | 0.006                | 0.010 |
| b2     | 0.250                         | 0.350 | 0.010                | 0.014 |
| c      | 0.100                         | 0.200 | 0.004                | 0.008 |
| D      | 1.500                         | 1.700 | 0.059                | 0.067 |
| E      | 0.700                         | 0.900 | 0.028                | 0.035 |
| E1     | 1.450                         | 1.750 | 0.057                | 0.069 |
| e      | 0.500TYP                      |       | 0.020TYP             |       |
| e1     | 0.900                         | 1.100 | 0.035                | 0.043 |
| L      | 0.400REF                      |       | 0.016REF             |       |
| L1     | 0.260                         | 0.460 | 0.010                | 0.018 |
| θ      | 0°                            | 8°    | 0°                   | 8°    |