

Features


- Leading trench technology for low $R_{DS(on)}$
- Low Gate Charge

Product Summary

V_{DS}	$R_{DS(ON)}$ MAX	I_D MAX
-20V	33mΩ@-4.5V	-5.9A
	55mΩ@-2.5V	



Application

- Video monitor
- Power management



2365E: Device code

Marking and pin assignment



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
--------	-----------	--------	------

Common Ratings (TC=25°C Unless Otherwise Noted)

V _{DS}	Drain-Source Breakdown Voltage		-20	V
V _{GS}	Gate-Source Voltage		±10	V
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range		-55 to 150	°C
I _S	Diode Continuous Forward Current	Tc=25°C	-5.9	A

Mounted on Large Heat Sink

I_{DM}	Pulse Drain Current Tested	$T_c=25^\circ\text{C}$	-23	A
I_D	Continuous Drain Current	$T_c=25^\circ\text{C}$	-5.9	A
P_D	Maximum Power Dissipation	$T_c=25^\circ\text{C}$	1.8	W
$R_{\theta JA}$	Thermal Resistance Junction-to-Ambient		90	°C/W

Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MLSK2365E	SOT-23-3L	2365E	3,000	45,000	180,000	7"reel

Electrical Characteristics (T _J =25°C unless otherwise noted)						
Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Electrical Characteristics @ T _J = 25°C (unless otherwise stated)						
B _{V(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	-20	–	–	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-20V, V _{GS} =0V	--	–	-1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±10V, V _{DS} =0V	--	–	±10	μA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-0.4	-0.8	-1.0	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =-4.5V, I _D =-4A	--	26	33	mΩ
		V _{GS} =-2.5V, I _D =-4A	--	40	55	mΩ
		V _{GS} =-1.8V, I _D =-2A	--	70	120	mΩ
Dynamic Electrical Characteristics @ T _J = 25°C (unless otherwise stated)						
C _{ISS}	Input Capacitance	V _{DS} =-10V, V _{GS} =0V, f=1MHz	–	540	–	pF
C _{OSS}	Output Capacitance		–	120	–	pF
C _{RSS}	Reverse Transfer Capacitance		–	100	–	pF
Switching Characteristics						
Q _g	Total Gate Charge	V _{DS} =-10V, I _D =-5A, V _{GS} =-4.5V	–	13	–	nC
Q _{gs}	Gate Source Charge		–	1.9	–	nC
Q _{gd}	Gate Drain Charge		–	2	–	nC
t _{d(on)}	Turn-on Delay Time	V _{DS} =-10V, R _L =2.5Ω, V _{GS} =-10V, R _G =2.2Ω	–	5	–	nS
t _r	Turn-on Rise Time		–	47	–	nS
t _{d(off)}	Turn-Off Delay Time		–	52	–	nS
t _f	Turn-Off Fall Time		–	69	–	nS
Source- Drain Diode Characteristics						
V _{SD}	Forward on voltage	T _J =25°C, I _S =-4A	--	–	-1.2	V

Typical Operating Characteristics




Fig1. Typical Output Characteristics




Fig2. Typical Gate Charge Vs. Gate-Source Voltage




Fig3. Drain-Source on Resistance




Fig4. Normalized On-Resistance Vs. Temperature




Fig5. Maximum Safe Operating Area







Fig6 Typical Capacitance Vs. Drain-Source Voltage

SOT-23-3L Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.042	0.050
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.042	0.046
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.112	0.120
E	1.500	1.700	0.060	0.068
E1	2.650	2.950	0.106	0.118
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°