


Features

- Trench Power LV MOSFET technology
- High Density Cell Design for Low $R_{DS(ON)}$
- High Speed switching

Application

- Battery protection
- Load switch
- Power management



MU0C20AP : Device code
 XXXX : Code


Marking and pin assignment

Product Summary

V_{DS}	$R_{DS(ON)}$ TYP	I_D
-20V	22mΩ@-4.5V	-20A
	27mΩ@-2.5V	



TO-252 top view



Schematic diagram



Pb-Free



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
Common Ratings (TC=25°C Unless Otherwise Noted)			
V_{DS}	Drain-Source Breakdown Voltage	-20	V
V_{GS}	Gate-Source Voltage	±10	V
T_J	Maximum Junction Temperature	150	°C
T_{STG}	Storage Temperature Range	-55 to 150	°C
I_S	Diode Continuous Forward Current	$T_C=25^\circ\text{C}$ -20	A

Mounted on Large Heat Sink

I_{DM}	Pulse Drain Current Tested	$T_C=25^\circ\text{C}$ -60	A
I_D	Continuous Drain Current	$T_C=25^\circ\text{C}$ -20	A
P_D	Maximum Power Dissipation	$T_C=25^\circ\text{C}$ 75	W
$R_{\theta JA}$	Thermal Resistance Junction-to-Ambient	60	°C/W

Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MU0C20AP	TO-252	MU0C20AP	2,500	5,000	35,000	13"reel

Electrical Characteristics (TJ=25°C unless otherwise noted)						
Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Electrical Characteristics @ TJ = 25°C (unless otherwise stated)						
BV _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	-20	--	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-20V, V _{GS} =0V	--	--	-1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±10V, V _{DS} =0V	--	--	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-0.4	-0.7	-1.0	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =-4.5V, I _D =-20A	--	22	28	mΩ
		V _{GS} =-2.5V, I _D =-10A	--	27	36	mΩ
Dynamic Electrical Characteristics @ TJ = 25°C (unless otherwise stated)						
C _{ISS}	Input Capacitance	V _{DS} =-9V, V _{GS} =0V, f=1MHz	--	1015	--	pF
C _{OSS}	Output Capacitance		--	138	--	pF
C _{RSS}	Reverse Transfer Capacitance		--	105	--	pF
Switching Characteristics						
Q _g	Total Gate Charge	V _{DS} =-9V, I _D =-5.6A, V _{GS} =-4.5V	--	11.3	--	nC
Q _{gs}	Gate Source Charge		--	2.3	--	nC
Q _{gd}	Gate Drain Charge		--	2.4	--	nC
t _{d(on)}	Turn-on Delay Time	V _{DD} =-9V, I _D =-1A, V _{GS} =-4.5V, R _G =2.5Ω	--	8.5	--	nS
t _r	Turn-on Rise Time		--	35.5	--	nS
t _{d(off)}	Turn-Off Delay Time		--	78	--	nS
t _f	Turn-Off Fall Time		--	58	--	nS
Source- Drain Diode Characteristics						
V _{SD}	Forward on voltage	Tj=25°C, Is=-20A	--	--	-1.2	V

Typical Operating Characteristics




Fig1. Typical Output Characteristics




Fig2. Typical Gate Charge Vs. Gate-Source Voltage




Fig3. Drain-Source on Resistance




Fig4. Normalized On-Resistance Vs. Temperature




Fig5. Maximum Safe Operating Area





Fig6. Typical Capacitance Vs. Drain-Source Voltage

TO-252 Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.635	0.770	0.025	0.030
c	0.450	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	4.830 REF.		0.190 REF.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.712	10.312	0.386	0.406
L1	2.900 REF.		0.114 REF.	
L2	1.400	1.700	0.055	0.067
L3	1.600 REF.		0.063 REF.	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.250 REF.		0.207 REF.	